

AddressRight™ DA^{95F} Addressing Printer



This Printer can use the W986 Conveyor/Stacker and the W864 dryer to increase your productivity and the quality of your job. Stacking the documents in a proper manner will avoid to match the envelopes and keep the benefit of the postal discounts.

The W864 dryer will allow to print at high quality and keep the benefit of the speed of the DA^{95F} printer, in addition of this, that will opens new opportunities for printer of other substrats.

» **'Fixed Head' inkjet printing technology**

Six print heads arranged in two banks, enable printing of all text and graphics in one pass. Resolutions of 150, 200, 300 & 600 dpi horizontal and 300dpi or 600 dpi vertical, allow printing of draft light, draft, letter light, letter, executive light and executive qualities. The printer has 12 internal, scaleable fonts plus it will print unlimited TrueType fonts with no effect on production speed. The DA^{95F} offers black and spot colour printing.

» **Fast, efficient, high productivity**

Address postcards at speeds of up to 30,000 per hour (6 lines of text). Handles a variety of sizes by automatically feeding materials from 76 x 127mm up to 355 x 390mm and up to 12.7mm thick.

The optional Conveyor/Stacker increases productivity even further.

» **Detachable feeder (FeedRight and standard feeder)**

The DA^{95F} can be used either on-line or off-line thanks to its detachable feeder. This means that with the feeder detached, the printer can be used on-line with inserters and other mail production systems.

» **Complete versatility**

Print onto a wide range of media including envelopes, postcards, leaflets, and brochures. Print graphics and barcodes including the RM4SCC barcode.

» **Save money by maximising postal discounts**

By using our optional FlexMail® software, you can earn postal discounts that will reduce your postage costs significantly on volume mailings.

FlexMail® also offers the options of de-duplication and address validation for your databases, again offering significant savings by not mailing to duplicated or non-existent addresses.



DA^{95F} Specifications



- » **Maximum Speed** Up to 30,000 items per hour (at 150dpi)
- » **Print Resolution** Up to 600 dpi
- » **Media Sizes (mm)**

Min	76 x 127
Max	335 x 390
Max Thickness	12.7mm
- » **Dimensions (mm)**

Height	571
Width	680
Depth	622
Weight	60kg
- » **Internal Fonts, Graphics & Barcodes** Better memory management - 32MB, means print more complex layouts, more reliability
- » **Resolution** Six print qualities: draft light, draft, letter light, letter, executive light and executive
- » **PC Control Panel Software** Monitor and control the printer from the PC; and get information such as piece count, current throughput and ink levels for each cartridge in the printer. Low ink management for print quality assurance
- » **Drivers** Localised by Pitney Bowes, UK English, French, German, Italian, Spanish, Dutch...ask for others
- » **Conveyor Stacker** Optional
- » **Media Transport** Auto calibrating paper sensor, DC motor and high resolution encoder, ergonomic knob
- » **Electrical** 220/240Vac, 50Hz
- » **Operation** Requires an IBM compatible PC running Microsoft Windows 3.1 with latest service pack up to XP
- » **Input Stack** Standard feeder 500 DL envelopes (unstuffed) or FeedRight Feeder
- » **Output Stack** Continuous with optional Conveyor Stacker
- » **Emulation** Hewlett Packard PCL5 subset
- » **Interfaces** USB 2.0, Ethernet
- » **Display Languages** UK English, French, German, Italian, Spanish, Dutch, Japanese... ask for others
- » **Ink** Different inkjet cartridges are better suited for different applications. Pitney Bowes can help you pick the inkjet cartridge that works best for you and your application.
- » **Did you know that...**

All inkjet cartridges are not the same. You have many different choices when it comes to inkjet cartridges for your printers. There is a wide variety of HP45A technology inks. There is no silver bullet when it comes to print quality - what works well in one print job may not work well in another. The key is to find the right combination of ink, settings and adjustments for a given print job to optimise print quality.

W986 Conveyor/Stacker specifications:

Height: 228mm
Width: 381mm
Length: 1.7m
Weight: 26.3kg

Stacker Stand:

Height: 762mm (max)
610mm (min)
Width: 381mm
Length: 914mm
Weight: 9kg

W864 Dryer: (without stand)

Height: 89mm
Width: 330mm
Length: 362mm
Weight: 8.2kg

Pitney Bowes Limited

Elizabeth Way, Harlow
Essex CM19 5BD
Tel: 08705 252525
Fax: 08705 449450
www.pitneybowes.co.uk